





DIFFERENTIAL OPTICAL SHADOW SENSOR CUBESAT MISSION

Andreas Zoellner, Stanford University

Contributors:

Stanford: Sasha Buchman, Grant D. Cutler, Dan B. DeBra, Eric Hultgren, Shally Saraf, Seiya Shimizu

University of Florida: John W. Conklin KACST: Ahmad Aljadaan, Hamoud Aljibreen









Drag-free Concept and Applications

 Cancel deviation from geodetic orbit



- Geodesy
- Aeronomy
- Autonomous orbit determination
- Fundamental Physics










Drag-free History

- TRIAD I (1972)
- GRACE (2002)*
- Gravity Probe B (2004)
- GOCE (2009)




- LISA Pathfinder
- LISA











^{*} Accelerometer only










The Drag-free CubeSat

- 3U CubeSat
- Demonstrate fully integrated MGRS
- 2y development time
- Areas of Research:
 - Drag-free control algorithm
 - In-orbit performance evaluation
 - Environmental modeling and optimization (thermal, electro-magnetic)












Modular Gravitational Reference Sensor (MGRS)



- Differential Optical Shadow Sensor (DOSS) to sense external disturbances
- UV LED for Charge
 Management to compensate
 internal disturbance
- Caging Mechanism designed for 200 N holding force
- Spinning Sphere for spectral shift of disturbances










Differential Optical Shadow Sensor (DOSS)

- 2U CubeSat
- Raise TRL
- Test Attitude Control Algorithms
- Designed for 1nm resolution at 10mHz-1Hz
- Completion: 2013












Subsystems












Shadow Sensor Electronics

- Low noise amplifier
- 8 channel 16-bit ADC
- DSP payload computer
- Low power design











Current Status

- COTS Parts:
 - CubeSat Kit purchased
- Custom Electronics:
 - First revision undergoes performance evaluation
- Sensor Housing:
 - Finalizing first design
- Space Qualification:
 - Shake and Bake scheduled end of summer

