

Summer 6-25-2014

Defects Density of States Model of Cathodoluminescent Intensity and Spectra of Disordered SiO₂

Amberly Evans Jensen
Utah State University

JR Dennison
Utah State University

Follow this and additional works at: https://digitalcommons.usu.edu/mp_presentations

 Part of the [Physics Commons](#)

Recommended Citation

Evans Jensen, Amberly and Dennison, JR, "Defects Density of States Model of Cathodoluminescent Intensity and Spectra of Disordered SiO₂" (2014). 13th Spacecraft Charging Technology Conference. *Presentations*. Paper 15.
https://digitalcommons.usu.edu/mp_presentations/15

This Presentation is brought to you for free and open access by the Materials Physics at DigitalCommons@USU. It has been accepted for inclusion in Presentations by an authorized administrator of DigitalCommons@USU. For more information, please contact rebecca.nelson@usu.edu.





Defects Density of States Model of Cathodoluminescent Intensity and Spectra of Disordered SiO₂

Amberly Evans Jensen and JR Dennison*

Materials Physics Group, Physics Department, Utah State University

Abstract

Electron beam measurements have shown that disordered SiO₂ exhibits luminescent behavior, which varies with incident beam energy and current density, sample temperature (T), exposure time, and wavelength. A simple model based on the electronic band structure and defect density of states—used to explain electron transport in highly disordered insulating materials—has been extended to predict the relative cathodoluminescent intensity and spectral radiance for disordered SiO₂ as a function of these variables.

Insulating SiO₂ has a band gap of ~8.9 eV. Hence thermal excitation from the valence to conduction band is highly improbable; excitation is through collisions of the incident high energy electrons. For visible and near-IR (NIR) light to be emitted, there must be other states within the forbidden band gap for electrons to occupy. These localized defect or “trap” states of disordered SiO₂ are due to structural defects or to substitutional chemical defects. The data were fit with the proposed model using saturation dose rate and mean shallow trap energy as fitting parameters, which can be compared with results from independent experiments.

Tests were conducted on two types of disordered SiO₂ samples: (i) thin (~60-200 nm) coatings on reflective metal substrates and (ii) ~80 μm thick bulk samples, much thicker than the electron penetration depth at the energies studied. Luminescence was measured using a visible range SLR CCD still camera, a VIS/NIR image-intensified video camera, a NIR video camera, and a UV/VIS spectrometer, each with NIST-traceable absolute calibration. Sample temperature was varied from ~295 K to 40 K.

The overall cathodoluminescence intensity depended on the incident electron energy and sample thickness, as predicted by the model. Each incident energy has a corresponding penetration depth, or range, which determines the fraction of energy absorbed in the material. In the thinner samples, the range exceeded the thickness of the sample; therefore, the intensity decreases with increasing energy. However, for the thicker samples, the range is less than the sample thickness and the intensity increased linearly with incident energy.

Cathodoluminescence intensity increased with incident current. At low current densities, luminescent intensity is linearly proportional to incident current density through the dose rate. At very high current densities, saturation can occur when trap states are filled, limiting the number of available states electrons can decay into. Thus, as current increased, the intensity increased until it reached a saturation dose rate on the order of 10² Gy/s for disordered SiO₂.

The overall luminescent intensity increased exponentially as T decreased, until it reached a crossover temperature (~45 K), where it began to decrease (as the model predicts). However, the spectral radiance showed there are four distinct bands, corresponding to four distinct energy distributions of defect states (defect bands) within the band gap; each behaved differently with temperature. The UV, blue and green band intensities increases with increasing T, while the red band intensity decreases. The red peak undergoes a red-shift in band peak wavelength as T increases, while the UV, blue and green bands undergo a blue-shift. Each of these relative temperature responses is indicative of the extent to which each band is filled. At low temperature the higher energy defect bands will be largely unoccupied, while those bands below the effective Fermi level will be mostly filled. As T increases, thermal energy excites electrons in lower bands into higher states, thus enhancing the probability for relaxation of conduction band and shallow trapped electrons into the lower bands and the emission of higher energy photons.

* Work supported through a NASA Science and Technology Research Fellowship, a Senior Research Fellowship from the National Research Council and AFRL, and funding from NASA Goddard Space Flight Center.

Amberly Evans Jensen and JR Dennison, “Defects Density of States Model of Cathodoluminescent Intensity and Spectra of Disordered SiO₂,” 13th Spacecraft Charging Technology Conference, (Pasadena, CA, June 25-29, 2014).