Utah State University DigitalCommons@USU

Posters

Materials Physics

5-15-2017

Enhanced Test Facility for Survivability and Characterization of Evolving Multiscale Materials in Extreme Plasma Environments

JR Dennison Utah State Univesity

Follow this and additional works at: https://digitalcommons.usu.edu/mp_post

Part of the Condensed Matter Physics Commons

Recommended Citation

JR Dennison, "Enhanced Test Facility for Survivability and Characterization of Evolving Multiscale Materials in Extreme Plasma Environments," 2017 Aerospace Materials for Extreme Environments Program Review, Air Force Office of Scientific Research, Kirtland Air Force Base, Albuquerque, NM, May 15, 2017.

This Conference Poster is brought to you for free and open access by the Materials Physics at DigitalCommons@USU. It has been accepted for inclusion in Posters by an authorized administrator of DigitalCommons@USU. For more information, please contact digitalcommons@usu.edu.



Overview

A major upgrade to the Utah State Space Environment University Effects Materials Test Facility is proposed. Ensuing research focuses on scientific models and wideranging applications related to the



evolution of complex materials (including layered and nanostructured materials and composites) due to exposure to extreme plasma environments, electric fields, temperatures, and vacuum. Two new synergistic vacuum test chambers will be developed, through the addition of novel instrumentation to existing systems. This will greatly enhance and extend our capabilities and ranges to investigate extreme environmental effects on materials and components and to determine longterm survivability of space assets

Current/Pending SEEM Projects

Current and pending projects employing the DURIP instrumentation cover a wide array of scientific fields; these include:

- Electrostatic discharge events induced by β-radiation in high frequency RF antenna dielectric components for telecommunications satellites. ViaSat funded.
- In-Situ permittivity characterization and long-term cumulative effects of β-radiation on high performance RF communications cabling accelerated testing of full multi-year mission. *Times* Microwave funded.
- VUV degradation of antennas and thermal control coatings. Aerospace company funded
- UV degradation of thermal control materials. Aerospace company funded.
- Radiation induced conductivity (RIC) of perovskite dielectric materials by total ionizing dose (TID). Sandia National Labs funding pending.
- Effects of radiation on conductivity and permittivity of space polymers for NASA Europa Mission. NASA Jet Propulsion Lab funding pending.
- Electron transport studies of spacecraft antenna coating materials. Aerospace company funding pending.
- Radiation Modification of Space Flight CCD Array. Space Dynamics Lab funded.
- Electron emission studies of thermal control coating materials. Aerospace company funding pending.
- Electron emission studies of low yield multipactor coating materials. Nokomis AFRL SBIR funded.
- Electron Emission Studies of Orion Backshell Materials. NASA and Lockheed Martin funded.
- COTS microcontrollers radiation hardening tests for CubeSat missions. USU Physics Funded. SparkFun funding pending.
- β radiation TID effects on electronic components. Aerospace company funding pending.
- Comparison of germination rates of radish seeds flown on Russian BION-M1 mission to simulated radiation and vibrations. Funded through DoEd USUStars Gear Up Program and Tsukuba University Japan Student Space Collaboration Program. Proposed funding through NASA BION-M2 mission.
- Space environment effects on muscle and skeletal cells through in-vitro tests of irradiated muscles cells. Funded through NASA USGC. Funding pending through NASA Space Radiobiology and Human Health Countermeasures Topics.
- Pre-flight space environment hybrid thruster tests for Terrier Malamute rocket mission. NASA Undergraduate Student Instrument Project (USIP) funding pending.

The SMART chamber probes electron emission, charging, and charge-transport properties of samples under extremes in electron-, ion-, and VUV/UV/Vis/NIR radiation-fluxes and cryogenic to high temperatures. Notable enhancements include: (i) multiple simultaneous electron and photon fluxes over extended energy ranges to test synergistic effects; (ii) enhanced capabilities for high-precision and high-accuracy electron-, ion- and photon-induced electron yield, emission and transport properties of conducting through extreme insulating materials; (iii) extended wavelength ranges, sensitivity, and imaging speed of absolute VUV/UV/Vis/NIR radiation detection for discharge and luminescence studies; (iv) extended range, sensitivity, and acquisition speed of surface voltage measurements; (v) VUV radiation for photoyield testing and radiation damage.

USU SMART Chamber

(a) Front view of chamber exterior showing full pumping well assembly. (b) Left isometric view of upper chamber. (c) Cutaway view of upper chamber showing the various sample stage and detector components. The sample position is at the intersection of the vertical chamber axis and the horizontal axis through the 8" flanges







USU SMART Chamber Components

Space Survivability Test (SST) Chamber

The SST chamber [2] is a high vacuum system particularly well suited for costeffective tests of multiple small scale materials samples over prolonged exposure critical environmental simulate to components. Exposure is uniform to within <5% at intensities for >5X accelerated testing. An automated data acquisition system periodically records real-time environmental conditions—and in situ monitoring of key satellite/component/sample performance metrics and characterization of material properties and calibration standards—during the sample exposure cycle [5].

Electron Radiation

A high energy (~10-80 keV) and three lower energy (~10 eV to 5 keV) electron guns provide ϵ high electron fluxes. Ionizing Radiation

100 mCi encapsulated Sr⁹⁰ β-radiation source (~200 keV to >2.5 MeV) mimics high energy (~250 keV to 2.5 MeV) geostationary electron flux. Infrared/Visible/Ultraviolet Flux

Commercial Class AAA solar simulator provides NIR/Vis/UVA/UVB electromagnetic radiation (from 200 nm to 1700 nm) at up to 4 times sun equivalent intensity.

Far Ultraviolet Flux

Kr resonance lamps provide FUV radiation flux (ranging from 10 to 200 nm) at 4X sun equivalent intensity.

Temperature Control

Temperature range from 60 K [4] to 450 K is maintained to ± 2 K [3].

Controlled Atmosphere and Vacuum

Ultrahigh vacuum chamber allows for pressures <10⁻⁷ Pa to simulate LEO.

Video Discharge Monitoring

Using custom developed software, live video capture and processing of electrostatic discharge events allows for real-time visual identification of discharge location, intensity, spectral range, and frequency.

Flexible Sample Mounting

Rotating graphite carousel, ensures uniform irradiation and allows for custom mounting of samples. Or a flange mounted fixture for electrostatic allows discharge testina Radiation source distance sample adjustable.

Biological Testing

Biological samples, which are vacuum incompatible, use a custom can designed chamber controlled atmosphere and temperature.







Acknowledgments and References

JR Dennison, K. Hartley, L. Phillipps, J. Dekany, J. S. Dyer, and R. H. Johnson, "Small Satellite Space Environments Effects Test Facility," Proc. 28th Annual AIAA/USU Conf. on Small Satellites, 2014. 2) R. Hoffmann and J. R. Dennison, "Methods to determine total electron- induced electron yields over broad range of conductive and nonconductive materials," IEEE Trans. on Plasma Sci., 40(2), 305–310, 2012. R. H. Johnson, L Montierth, JR Dennison, J. S. Dyer, and E. Lindstrom, "Small Scale Simulation Chamber

- for Space Environment Survivability Testing," IEEE Trans. on Plasma Sci., 41(12), 3453-3458, 2013. 4) J. Dekany, R. H. Johnson, G. Wilson, A. Evans and JR Dennison, "Ultrahigh Vacuum Cryostat System for Extended Low Temperature Space Environment Testing," IEEE Trans. on Plasma Sci., 42(1), 266-271, 2014.
- 5) A. Jensen, G. Wilson, J. Dekany, A. M. Sim and JR Dennison "Low Temperature Cathodoluminescence of Space Observatory Materials," IEEE Trans. on Plasma Sci., 42(1), 305-310, 2014. 6) J. L. Hodges, Alec M. Sim, Justin Dekany, Gregory Wilson, Amberly Evans, and JR Dennison "In Situ
- Surface Voltage Measurements of Layered Dielectrics," IEEE Trans. on Plasma Sci., 42(1), 255-265, 2014. 7) G. Wilson and JR Dennison, "Hemispherical Grid Retarding Field Analyzer Redesign for Secondary Electron Emission Studies," Proc. Utah NASA Space Grant Consortium Research Symp., Ogden, UT, 9 pp., 2017.







access USU MPG articles and presentations. http://digitalcomm ons.usu.edu/mp/