Utah State University
DigitalCommons@USU

Research on Capitol Hill

Browse Undergraduate Research Events

2017

Groundwater Influences on the Logan River Watershed

Hyrum Tennant Utah State University

Follow this and additional works at: https://digitalcommons.usu.edu/roch

Recommended Citation

Tennant, Hyrum, "Groundwater Influences on the Logan River Watershed" (2017). *Research on Capitol Hill.* Paper 62.

https://digitalcommons.usu.edu/roch/62

This Article is brought to you for free and open access by the Browse Undergraduate Research Events at DigitalCommons@USU. It has been accepted for inclusion in Research on Capitol Hill by an authorized administrator of DigitalCommons@USU. For more information, please contact digitalcommons@usu.edu.



Groundwater Influences on the Logan River Watershed

Hyrum Tennant Utah State University

Dr. Bethany Neilson Utah State University

Introduction

Understanding the relationship between groundwater and surface water is key to water management. Within the Logan River watershed, it has been estimated that groundwater travels 7.2 miles in 8 to 31 days; this is attributed to the karst geology present within the watershed. Because of short travel times, groundwater is potentially a highly variable source of water within the watershed. Drinking water for Logan City and secondary water for northern Cache Valley are obtained from Dewitt Springs and the Logan River, respectively. Understanding the role of groundwater on surface water is key to managing the watershed as a sustainable water source. A simple flow balance over portions of 2015-2016 within the Logan River watershed provides a first cut understanding of groundwater influences on surface water over time and space.

UtahState University

Methods

- Five sub-reaches spanning the Logan River watershed were established (Figure 1).
- Continuous flow data at 16 significant tributaries, diversions, and main-stem sites were collected (Figure 2,3).
- The daily flow average at each site was calculated.
- The groundwater discharge/recharge was determined in each sub-reach using a flow balance (Figure 4).



Figure 1: Logan River watershed and sampling sites

This work is supported through the NSF iUTAH grant (EPS – 1208732), the U.S. Geological Survey, the Utah Division of Water Rights, the Utah Water Research Laboratory, and the Utah State University Office of Research and Graduate Studies. Special thanks to Michelle Barnes, Trinity Stout, Mitchell Rasmussen, Leah Richardson, Tyler King, Milada Majerova, Dave Epstein, Michelle Baker, Chris Cox, and the many iUTAH research fellows who helped with flow measurements.

Results

- Flows were steady from August to March and peaked with snowmelt in spring (Figure 5).
- Flows increased moving down the watershed.
- Consistent groundwater discharge to the river was observed in sub-reaches
 a, b, c, and e (Figure 6).
- Significant groundwater recharge occurred across the bench area in sub-reach d.

Figure 4: Flow balance representation



Discussion

These results indicate that the Logan River watershed is heavily influenced by groundwater. Climate change will affect the availability of shallow and deep groundwater over time. Future work should focus on quantifying deep and shallow groundwater flowpath contributions. Understanding these flowpaths is critical to maintaining the Logan River watershed as a sustainable drinking and secondary water source.

Hyrum Tennant Utah State University Civil and Environmental Engineering Department hyrumtennant@gmail.com

