

Utah State University

DigitalCommons@USU

Presentations

Materials Physics

3-13-2017

Model for Charge Injection with Electron Beams Into Highly Disordered Insulating Materials

JR Dennison
Utah State University

Follow this and additional works at: https://digitalcommons.usu.edu/mp_presentations

 Part of the [Condensed Matter Physics Commons](#)

Recommended Citation

Dennison, JR, "Model for Charge Injection with Electron Beams Into Highly Disordered Insulating Materials" (2017). *Presentations*. Paper 171.

https://digitalcommons.usu.edu/mp_presentations/171

This Presentation is brought to you for free and open access by the Materials Physics at DigitalCommons@USU. It has been accepted for inclusion in Presentations by an authorized administrator of DigitalCommons@USU. For more information, please contact digitalcommons@usu.edu.



2017 March Meeting of the
American Physical Society



*New Orleans, LA
March 13-17, 2017*

***Model for Charge Injection with Electron Beams
into Highly Disordered Insulating Materials***

JR Dennison

Physics Department, Utah State University

Abstract

The Walden-Wintle model for charge injection and transport through highly disordered insulating materials has been extended to include charge injection with a charged particle beam. The original model is applicable to charge injection into a dielectric material from a pair of electrodes in a parallel-plate geometry. It provides a versatile approach to predict the time-dependent current at a rear grounded electrode and the incident surface voltage, as the injection current density evolves over time with the development of a space charge barrier near the injection electrode. The Walden-Wintle model has been applied to many standard cases including Fowler-Nordheim injection, Schottky injection, space charge limited injection, and various tunneling mechanisms. The present model modifies the approach to include electrode-less charge injection via a charged particle beam, along with concomitant effects for the injection current, surface voltage, and electron emission as a charge is built up in the insulator. The approach is equally valid for near-surface injection and for bulk injection of both non-penetrating and penetrating radiation. The results are based on our dynamic emission model for electron emission yields dependent on accumulating charge in both the positive and negative charging regimes.

*This work was supported by funds from NASA Goddard Space Flight Center and NRC Senior Research Fellowship at AFRL.